## 50000 Counts Dual Display Digital Multimeter



The GDM-8245 is an economical bench-top DMM equipped with a rich set of features. The GDM-8245 has similar functions to the GDM-8246, but with slightly reduced DCV accuracy and no communication interfaces. The large 7 segment LED dual display features up to 50,000 counts and the ability to show two measurements at extensive list of measurement items - DC Voltage/Current, AC Voltage/Current with true RMS, Resistance, Capacitance, Frequency, Continuity (with beeper), Diode Test, and dBm. Additional measurement functions, such as Max/Min hold, Relative value, and Compare ease setup and diagnosis burdens. With great range, good accuracy and able to accept up to 20A of current the GDM-8245 is the perfect general purpose DMM.

### **GDM-8245 (50000 Counts)**



#### **FEATURES**

- \* 50000 Counts Display
- \* Multi-Function ACV, DCV, ACA, DCA, R, C, Hz, Continuity Beeper, Diode Test, Max/Min, REL, Hold, dBm
- \* Dual Display Indicate ACV and Hz, DCV(ACV) and dBm
- \* Manual or Auto Ranging
- \* 0.03% DCV Accuracy
- \* ACV Measuring Frequency Up to 50kHz
- \* AC True RMS or AC + DC True RMS

#### **Rear Panel**



#### GTL-117 Test Lead



SPECIFICATIONS	
DC VOLTAGE	
Range	500mV, 5V, 50V, 500V, 1000V 5 ranges
Accuracy	$\pm$ (0.03% rdg + 4 digits)
Input Impedance	10ΜΩ
AC VOLTAGE TRUE RMS (AC OR AC + DC TRUE RMS)	
Range	500mV, 5V, 50V, 500V, 1000V 5 ranges
Accuracy	500mV ~ 50V 3 ranges : 20Hz ~ 45Hz : ±(1% rdg + 15 digits)
	$45$ Hz $\sim 2$ kHz $\pm (0.5\% \text{ rdg} + 15 \text{ digits})$
	2k~10kHz± (1% rdg + 15 digits)
	10kHz ~ 20kHz± (2% rdg + 30 digits)
	$20kHz \sim 50kHz\pm (5\% rdg + 30digits)$
	500V,1000V range:
	$45$ Hz ~ $1$ kHz $\pm$ (0.5% rdg + 15 digits)
Input Impedance	10ΜΩ
DC CURRENT	
Range	500 μA, 5mA, 50mA, 500mA, 2A, 20A 6 ranges
Accuracy	500 μA~500mA 4ranges: <u>±</u> (0.02% rdg+2 digits);2A~20A 2ranges: <u>±</u> (0.3% rdg+2digits)
AC CURRENT TRUE	RMS (AC OR AC + DC TRUE RMS)
Range	500 μA, 5mA, 50mA, 500mA, 2A, 20A 6 ranges
Accuracy	500 μA ~ 20A 6 ranges
	20Hz ~ 45Hz : ±(1% rdg + 15 digits) ; 45Hz ~ 2kHz :±(0.5%rdg + 15 digits)
	$500 \mu A \sim 50 mA 3 \text{ ranges}$ $2 kHz \sim 10 kHz : \pm (1\% \text{ rdg} + 15 \text{ digits}) ; 10 kHz \sim 20 kHz : \pm (2\% \text{ rdg} + 15 \text{ digits})$
D-010-1110-	2KH2 ~ 10KH2 (1/6/10g + 13 digits) , 10KH2 ~ 20KH2 (2/6/10g + 13 digits)
RESISTANCE	
Range	$500\Omega$ , $5k\Omega$ , $500k\Omega$ , $500k\Omega$ , $5M\Omega$ , $20M\Omega$ 6 ranges
Accuracy	$500\Omega$ : $\pm (0.1\% \text{ rdg} + 4 \text{ digits})$ ; $5k\Omega \sim 500k\Omega$ 3 ranges : $\pm (0.1\% \text{ rdg} + 2 \text{ digits})$
	$5M\Omega$ : $\pm$ (0.2% rdg + 2 digits); $20M\Omega$ : $\pm$ (0.3% rdg + 2 digits)
DIODE TEST	
	The one range can check the forward voltage of diode. Maximum forward voltage 1.5V
CARACITANICE	open voltage 2.8V
CAPACITANCE	
Range	5nF, 50nF, 500nF, 5μF, 50μF 5 ranges
Accuracy	± (2% rdg + 4 digits)
FREQUENCY	ma// margar 1011
Input Level (Sine Wave)	mV range : 10Hz ~ 50kHz : >120mV ; 50k ~ 150kHz : >200mV 5V ~ 50V range : 10Hz ~ 200kHz >1.2V ; 500V range : 20Hz ~ 1kHz >12V
FUNCTIONS	5
	Auto Manual/Range, Max, Min, dBm, REL, Hold
CONTINUITY BEEP	, ,
	Built in buzzer sounds when conductance is less than 5 $\Omega$
DISPLAY	
Dual Display 0.4" and 0.5", 7 segment LED display	
POWER SOURCE	· · · · · · · · · · · · · · · · · · ·
AC 100V/120V/230V±10%, 50/60Hz	
DIMENSIONS & WEIGHT	
251(W) x 91(H) x 291(D) mm, Approx. 2.6kg	

#### ORDERING INFORMATION

GDM-8245 50,000 Counts Dual Display Digital Multimeter

ACCESSORIES:

User manual x 1, Power cord x 1, Test lead GTL-117 x 1

## **Available from**



# Power sources and test instrumentation solutions

Caltest have been providing power sources and test instrumentation solutions for over 20 years and are proud to represent a number of industry leading manufacturers.

As well as supplying world class power sources and test instrumentation Caltest also has a service centre and UKAS calibration laboratory.

NEED HELP?
CALL US:
01483 302 700

or visit our website for more details

Caltest Instruments Ltd 4 Riverside Business Centre Walnut Tree Close Guildford Surrey GU1 4UG United Kingdom Tel: +44 (0) 1483 302 700 Fax: +44 (0) 1483 300 562 sales@caltest.co.uk www.caltest.co.uk

Sales • Rentals • Service • UKAS Calibration

