



The GOM-802 milliohm meter is designed for component and material impedance measurements in laboratories and other test environments. A large display with 30,000 counts and a superb accuracy of up to 0.05% gives the reliability and flexibility required in demanding measurement applications. Features such as Auto ranging, a built-in comparator offering Hi-Lo testing, a Limit Percent setting, and Go/NoGo testing reduce the effort for complex testing setups. Displayed selections of Relative, Actual, and % Value show results viewed from multiple perspectives. The GOM-802 supports 4 Wire Kelvin resistance measurements for faster accurate results. For an accurate, sophisticated, affordable milliohm meter, the GOM-802 is the right choice.

GOM-802




FEATURES

- * 30000 Counts Display
- * High Accuracy 0.05%
- * Hi/Lo Comparator and Limit Percent Setting
- * Measurement of REL, Actual and % Value
- * Continuous or Triggered Measurement Mode
- * Temperature Compensation and Measurement
- * Four-Terminal Measurement Technique
- * Auto-Recall Last Setting Before Power OFF
- * Alarm Setting for PASS/FAIL
- * Scan, Handler Interface (Standard)
- * Manual or Autoranging
- * RS-232C+GPIB (Option)

GTL-108A Test Lead

For: GOM-801H/802 , GDM-8255A/8251A



PT-100 Temperature Probe

For: GOM-802



Rear Panel



SPECIFICATIONS

DISPLAY	
	30,000 counts
RESISTANCE	
Ranges/Test Current (Fixed)	30mΩ /1A 300mΩ/100mA 3Ω/100mA
	30Ω /10mA 300Ω/1mA 3kΩ/100μA
	30kΩ /100μA 300kΩ/10μA 3MΩ/1μA
Accuracy	30mΩ : ±0.1% reading + 6 digits 300mΩ : ±0.05% reading + 6 digits 3Ω : ±0.05% reading + 3 digits 30Ω - 3MΩ : ±0.05% reading + 2 digits
Resolution	1 μΩ , 10 μΩ , 100 μΩ , 1mΩ , 10mΩ , 100mΩ , 1Ω , 10Ω , 100Ω
TEMPERATURE	
Ranges	-50 °C - 100 °C
Accuracy	-10 °C - 40 °C : 0.3% + 0.5 °C other : 0.3% + 1.0 °C
Resolution	0.1 °C
FUNCTION	
	Hi/Lo, Go/No-Go, Manual Trigger, Actual, %, Diode, Temp, TC for Transformer
MEASURING RATE	
	7 measuring / sec at 30,000 counts , 30 measuring / sec at 3,000 counts
MEMORY	
	20 sets
INTERFACE	
	Standard : Handler / Scan (same connector) Option : RS-232C+GPIB
POWER SOURCE	
AC 100/120/220/230V ±10% , 50/60Hz	
DIMENSIONS & WEIGHT	
251 (W) x 91 (H) x 291 (D)mm, Approx. 3kg	

ORDERING INFORMATION

GOM-802 High Precision Programmable DC Milli-Ohm Meter

ACCESSORIES :

User manual x 1 , Power cord x 1 , Test lead GTL-108A x 1

OPTION

Opt.01 RS-232C + GPIB Interface (Factory Installed)

OPTIONAL ACCESSORIES

PT-100 Platinum Temperature Probe

GTL-232 RS232C Cable, 9-pin Female to 9-pin, null Modem for Computer

FREE DOWNLOAD

Driver LabView Driver

Available from



CALTEST
Instruments Ltd
Specialists in power
and instrumentation

Power sources and test instrumentation solutions

Caltest have been providing power sources and test instrumentation solutions for over 20 years and are proud to represent a number of industry leading manufacturers.

As well as supplying world class power sources and test instrumentation Caltest also has a service centre and UKAS calibration laboratory.

NEED HELP?

CALL US:

01483 302 700

or visit our website for more details

Caltest Instruments Ltd
4 Riverside Business Centre
Walnut Tree Close
Guildford
Surrey GU1 4UG
United Kingdom

Tel: +44 (0) 1483 302 700

Fax: +44 (0) 1483 300 562

sales@caltest.co.uk

www.caltest.co.uk

Sales • Rentals • Service • UKAS Calibration

